

# **LED Wash Bar Light 4in1**

## **10w×18 Pixel Control**

(製品番号 : bar-10wx18-pixel)

### **取扱説明書**



## 1.キーとディスプレイの機能



MENU : 機能を順番に切り替え

UP : 値を増加

DOWN : 値を減少

ENTER : 設定を保存

## 2.ディスプレイ表示

No.	Show	Function
1	CH6/9/29/77	DMX mode CH6,CH9,CH29,CH77 selection
2	d001	DMX512 Address ; B,C button to add /reduce value
3	R255	Red Dimming, (暗→明)
4	G255	Green Dimming, (暗→明)
5	B255	Blue Dimming, (暗→明)
6	H255	White Dimming, (暗→明)
7	P255	Yellow color dimming, (暗→明)
8	Pr01	内蔵プログラム選択 (Pr01-Pr30)
9	SP01	プログラム実行速度 (SP01-SP16)
10	Auto/Audi	テストモード : Auto またはサウンドコントロール
11	EP00/01	DMX 信号保持設定
12	DISP	ディスプレイ表示の向き (通常/反転)

### 3.DMX512 設定

#### 6 チャンネルモード

Channel	DMX Value	Function
CH1	000-255	RGBW Main Dimming, (暗→明)
CH2	000-255	RGBW Strobe, Speed (遅→速)
CH3	000-255	Red Dimming, (暗→明)
CH4	000-255	Green Dimming, (暗→明)
CH5	000-255	Blue Dimming, (暗→明)
CH6	000-255	White Dimming, (暗→明)

#### 9 チャンネルモード

Channel	DMX Value	Function
CH1	000-255	RGBW Main Dimming, From dark to bright
CH2	000-255	RGBW Strobe, Speed (遅→速)
CH3	000-255	Red Dimming, (暗 → 明)
CH4	000-255	Green Dimming, (暗 → 明)
CH5	000-255	Blue Dimming, (暗 → 明)
CH6	000-255	White Dimming, (暗 → 明)
CH7	000-255	RGBW Color mixing
CH8	000-255	内蔵プログラム (0-21: CH1-CH7 有効、22-255: プログラム)
CH9	000-255	プログラム速度 (速い → 遅い)

## 29 チャンネルモード

Channel	DMX Value	Function
CH1	000-255	RGBW Main Dimming, (暗 → 明)
CH2	000-255	RGBW Strobe, Speed (遅 → 速)
CH3	000-255	Group1 Red color linear dimming, (暗 → 明)
CH4	000-255	Group1 Green color linear dimming, (暗 → 明)
CH5	000-255	Group1 Blue color linear dimming, (暗 → 明)
CH6	000-255	Group1 White color linear dimming, (暗 → 明)
CH7	000-255	Group2 Red color linear dimming, (暗 → 明)
CH8	000-255	Group2 Green color linear dimming, (暗 → 明)
CH9	000-255	Group2 Blue color linear dimming, (暗 → 明)
CH10	000-255	Group2 White color linear dimming, (暗 → 明)
CH11	000-255	Group3 Red color linear dimming, (暗 → 明)
CH12	000-255	Group3 Green color linear dimming, (暗 → 明)
CH13	000-255	Group3 Blue color linear dimming, (暗 → 明)
CH14	000-255	Group3 White color linear dimming, (暗 → 明)
CH15	000-255	Group4 Red color linear dimming, (暗 → 明)
CH16	000-255	Group4 Green color linear dimming, (暗 → 明)
CH17	000-255	Group4 Blue color linear dimming, (暗 → 明)
CH18	000-255	Group4 White color linear dimming, (暗 → 明)
CH19	000-255	Group5 Red color linear dimming, (暗 → 明)
CH20	000-255	Group5 Green color linear dimming, (暗 → 明)
CH21	000-255	Group5 Blue color linear dimming, (暗 → 明)
CH22	000-255	Group5 White color linear dimming, (暗 → 明)
CH23	000-255	Group6 Red color linear dimming, (暗 → 明)
CH24	000-255	Group6 Green color linear dimming, (暗 → 明)
CH25	000-255	Group6 Blue color linear dimming, (暗 → 明)
CH26	000-255	Group6 White color linear dimming, (暗 → 明)
CH27	000-255	RGBW Color mixing
CH28	000-255	内蔵プログラム (0-21: CH1-CH7有効、22-255: プログラム)
CH29	000-255	Built-in Program speed, (遅 → 速)

備考: 合計 18 個の LED、3 個ごとに 1 グループ、合計 6 グループ。

## 77 チャンネルモード

Channel	DMX Value	Function
CH1	000-255	RGBW Main Dimming, (暗 → 明)
CH2	000-255	RGBW Strobe, Speed (遅→速)
CH3	000-255	LED 1# Red color linear dimming, (暗 → 明)
CH4	000-255	LED 1# Green color linear dimming, (暗 → 明)
CH5	000-255	LED 1# Blue color linear dimming, (暗 → 明)
CH6	000-255	LED 1# White color linear dimming, (暗 → 明)
CH7	000-255	LED 2# Red color linear dimming, (暗 → 明)
CH8	000-255	LED 2# Green color linear dimming, (暗 → 明)
CH9	000-255	LED 2# Blue color linear dimming, (暗 → 明)
CH10	000-255	LED 2# White color linear dimming, (暗 → 明)
CH11	000-255	LED 3# Red color linear dimming, (暗 → 明)
CH12	000-255	LED 3# Green color linear dimming, (暗 → 明)
CH13	000-255	LED 3# Blue color linear dimming, (暗 → 明)
CH14	000-255	LED 3# White color linear dimming, (暗 → 明)
CH15	000-255	LED 4# Red color linear dimming, (暗 → 明)
CH16	000-255	LED 4# Green color linear dimming, (暗 → 明)
CH17	000-255	LED 4# Blue color linear dimming, (暗 → 明)
CH18	000-255	LED 4# White color linear dimming, (暗 → 明)
CH19	000-255	LED 5# Red color linear dimming, (暗 → 明)
CH20	000-255	LED 5# Green color linear dimming, (暗 → 明)
CH21	000-255	LED 5# Blue color linear dimming, (暗 → 明)
CH22	000-255	LED 5# White color linear dimming, (暗 → 明)
CH23	000-255	LED 6# Red color linear dimming, (暗 → 明)
CH24	000-255	LED 6# Green color linear dimming, (暗 → 明)
CH25	000-255	LED 6# Blue color linear dimming, (暗 → 明)
CH26	000-255	LED 6# White color linear dimming, (暗 → 明)
...	...	...
CH67	000-255	LED 17# Red color linear dimming, (暗 → 明)
CH68	000-255	LED 17# Green color linear dimming, (暗 → 明)
CH69	000-255	LED 17# Blue color linear dimming, (暗 → 明)
CH70	000-255	LED 17# White color linear dimming, (暗 → 明)
CH71	000-255	LED 18# Red color linear dimming, (暗 → 明)
CH72	000-255	LED 18# Green color linear dimming, (暗 → 明)
CH73	000-255	LED 18# Blue color linear dimming, (暗 → 明)
CH74	000-255	LED 18# White color linear dimming, (暗 → 明)
CH75	000-255	RGBW Color mixing
CH76	000-255	内蔵プログラム (0-21: CH1-CH7 有効、22-255: プログラム)
CH77	000-255	Built-in Program speed, (速→遅)

## 製品仕様

電源電圧	AC 100-240V, 50-60Hz
消費電力	180W
光源	10W RGBW 4in1 LED × 18 個
制御	各 LED を個別にコントロール可能
制御モード	DMX / マスター・スレーブ / オート / サウンドコントロール
チャンネル数	6 / 9 / 29 / 77CH
レンズ角度	30°
エフェクト機能	ディマー、ストロボ、エフェクト、グラデーションチェンジ
冷却方式	インテリジェント冷却システム
ディスプレイ	デジタルスクリーン
保護機能	過熱保護機能付き
寸法	100 × 8.8 × 17 cm
本体重量	5.5kg