

LED Moving Head MINI 40w x7 4in1

(製品番号 CR1D102)

取扱説明書



添付品

- ・LED ムービングヘッド本体
- ・パワコン IN

スペック

LED	7x40W RGBW 4in1 LED
DMX チャンネル	35/23/51ch
カラー 色温度	RGBW 4in1 2800K-8500K
操作方法	DMX512 オートモード サウンドアクティブ マスタスレーブ
使用電圧	AC100V-240V 50-60Hz
消費電力	350W
本体サイズ	270×185×345mm
重量	9.7kg
ビームアングル	4.5-45°
回転	PAN540°(16bit) TILT270°(16bit)

MENU

DMX Address	000 - 512		
Fixture	Dmx Mode	35CH/23CH/51CH	
	Run Mode	DMX / Host / Sound	
	Pan Invert	Close / Open	
	Tilt Invert	Close / Open	
	Sound Control	1 -- 30	
Manual	Pan	000-255	
	Pan Fine	000-255	
	Tilt	000-255	
	Tilt Fine	000-255	
	...	...	
Information	Time	Current Time	xxxH
		Total Time	xxxH
	Sensor	Pan	FALSE / TURE
		Tilt	FALSE / TURE
		Zoom	FALSE / TURE
		Temp	FALSE / TURE
		Fan	FALSE / TURE
	Temperature	Head Temp	xxxC
	Software Version	Panel	Vx.xx
Factory	Password	000-255	
	Pan	000-255	
	Tilt	000-255	
	Zoom	000-255	
	Zoom Rotation	000-255	

	Red	000-255	
	Green	000-255	
	Blue	000-255	
	White	000-255	
Fixture Reset	Motor Reset	Cance / Run	
	Factory	Cance / Run	
Display	Language	CH / EN	
	Display Flip	Normal / Reverse	
	Display Mode	60s / Show	

DMX チャンネル表

35ch モード

1	Red	0 - 255	Red dimming
2	Red fine	0 - 255	Red fine turning
3	Green	0 - 255	Green dimming
4	Green fine	0 - 255	Green fine turning
5	Blue	0 - 255	Blue dimming
6	Blue fine	0 - 255	Blue fine turning
7	White	0 - 255	White dimming
8	White fine	0 - 255	White fine turning
9	Linear CTO	0 - 255	Linear color temperature regulation
10	Macro Color	0 - 255	Color macro function
11	Strobe	0 - 3	Lighting off
		4 - 103	Synchronous strobe speed is ranging from slow to fast
		104 - 107	Light up
		108 - 207	Flat-split strobe speed is ranging from slow to fast
		208 - 212	Light up
		213 - 225	Low speed random flash
		226 - 238	Medium speed random flash
		239 - 251	High speed random flash
		252 - 255	Light up
12	Dimmer	0 - 255	Linear dimming occurs from dark to light
13	Dimmer fine	0 - 255	Tuning fine-tuning control
14	Pan	0 - 255	Horizontal control
15	Pan fine	0 - 255	Horizontal fine-tuning control
16	Tilt	0 - 255	Vertical control
17	Tilt fine	0 - 255	Vertical fine-tuning control
18	Function	0 - 255	Obligate
19	Reset	0 - 250	NF
		251 - 255	The lamp body reset was valid for 5s
20	Zoom	0 - 255	Focus
21	Zoom rotation	0 - 127	0 ~ 60 degrees
		128 - 190	Clockwise polar rotation
		191 - 192	Stop
		193 - 255	Counterclockwise and infinite rotation

22	Shape selection	0 - 255	Shape rotation
23	Shape speed	0 - 255	Shape effect speed control
24	Shape fade	0 - 255	Shape effect is downplayed
25	Shape R	0 - 255	The shape effect is red
26	Shape G	0 - 255	The shape effect is green
27	Shape B	0 - 255	The shape effect is blue
28	Shape W	0 - 255	The shape effect is white
29	Shape dimmer	0 - 255	The effect with 0-100% dimming
30	Background dimmer	0 - 255	Background for 0-100% dimming
31	Shape transition	0 - 255	The shape effect change control
32	Shape offset	0 - 255	The effect angle adjustment
33	Foreground strobe	0 - 255	Foreground strobe
34	Background strobe	0 - 255	Background strobe
35	Background select	0 - 255	Background selection

23ch モード

1	Pan	0 - 255	Horizontal control
2	Pan fine	0 - 255	Horizontal fine-tuning control
3	Tilt	0 - 255	Vertical control
4	Tilt fine	0 - 255	Vertical fine-tuning control
5	P&T speed	0 - 255	P&T speed from fast to slow
6	Zoom	0 - 255	Foucus
7	Zoom rotation	0 - 127	0 ~ 60 degrees
		128 - 190	Clockwise polar rotation
		191 - 192	Stop
		193 - 255	Counterclockwise and infinite rotation
8	Dimmer	0 - 255	Linear dimming occrus from dark to light
9	Strobe	0 - 3	Lighting off
		4 - 103	Synchronous strobe speed is ranging from slow to fast
		104 - 107	Light up
		108 - 207	Flat-split strobe speed is ranging from slow to fast
		208 - 212	Light up
		213 - 225	Low speed random flash
		226 - 238	Medium speed random flash
		239 - 251	High speed random flash
		252 - 255	Light up
10	Red	0 - 255	Red dimming
11	Green	0 - 255	Green dimming
12	Blue	0 - 255	Blue dimming
13	White	0 - 255	White dimming
14	Linear CTO	0 - 255	Linear color temperature regulation
15	Macro Color	0 - 255	Color macro function
16	Static effect	0 - 255	Static effect
17	Dynamic effect	0 - 255	Dynamic effect
18	Effect speed	0 - 255	Effect speed

19	Background R	0 - 255	The background is red
20	Background G	0 - 255	The background is green
21	Background B	0 - 255	The background is blue
22	Background W	0 - 255	The background is white
23	Reset	0 - 250	NF
		251 - 255	The lamp body reset was valid for 5s

51ch モード

1	Pan	0 - 255	Horizontal control
2	Pan fine	0 - 255	Horizontal fine-tuning control
3	Tilt	0 - 255	Vertical control
4	Tilt fine	0 - 255	Vertical fine-tuning control
5	P&T speed	0 - 255	P&T speed from fast to slow
6	Zoom	0 - 255	Foucus
7	Zoom rotation	0 - 127	0 ~ 60 degrees
		128 - 190	Clockwise polar rotation
		191 - 192	Stop
		193 - 255	Counterclockwise and infinite rotation
8	Dimmer	0 - 255	Linear dimming occrus from dark to light
9	Strobe	0 - 3	Lighting off
		4 - 103	Synchronous strobe speed is ranging from slow to fast
		104 - 107	Light up
		108 - 207	Flat-split strobe speed is ranging from slow to fast
		208 - 212	Light up
		213 - 225	Low speed random flash
		226 - 238	Medium speed random flash
		239 - 251	High speed random flash
		252 - 255	Light up
10	Red	0 - 255	Red dimming
11	Green	0 - 255	Green dimming
12	Blue	0 - 255	Blue dimming
13	White	0 - 255	White dimming
14	Linear CTO	0 - 255	Linear color temperature regulation
15	Macro Color	0 - 255	Color macro function
16	Static effect	0 - 255	Static effect
17	Dynamic effect	0 - 255	Dynamic effect
18	Effect speed	0 - 255	Effect speed
19	Background R	0 - 255	The background is red
20	Background G	0 - 255	The background is green
21	Background B	0 - 255	The background is blue
22	Background W	0 - 255	The background is white
23	Reset	0 - 250	NF
		251 - 255	The lamp body reset was valid for 5s
24	R1 led dimming	0 - 255	R1 led dimming
25	G1 led dimming	0 - 256	G1 led dimming
26	B1 led dimming	0 - 257	B1 led dimming
27	W1 led dimming	0 - 258	W1 led dimming

.....			
48	R7 led dimming	0 - 255	R7 led dimming
49	G7 led dimming	0 - 256	G7 led dimming
50	B7 led dimming	0 - 257	B7 led dimming
51	W7 led dimming	0 - 258	W7 led dimming